

Lecture 07

Control Flow Instructions

CS213 – Intro to Computer Systems
Branden Ghena – Winter 2025

Slides adapted from:
St-Amour, Hardavellas, Bustamente (Northwestern), Bryant, O'Hallaron (CMU), Garcia, Weaver (UC Berkeley)

Pack Lab due today

- About half of the class is already done (110/234)
 - Some of those might still be working on extra credit
- Remember to test on the files in `example_files/`
 - If you can correctly unpack all of those, you'll end up getting a good grade
- Remember that you have 3 slip days
 - Spending one or two here isn't the end of the world
 - You don't need to ask to use them, we'll automatically apply them instead of late penalties
- Be sure to mark your partner on Gradescope after submitting

Administrivia

- Midterm exam in 1.5 weeks
 - Class time on Thursday (February 6th)
 - Covers everything from the start of class through Procedures (all of this week)
 - Does NOT cover pointers, arrays, and structs (Tuesday lecture right before it)
 - Bring a pencil and one 8.5"x11" inch paper with notes
 - Notes can be on both sides, handwritten or typed
 - No calculators
 - Practice exams (and solutions) are on the Canvas home page
 - Also good practice: Homework 2 (due Thursday), phases 1-3 of Bomb Lab

Get started on Bomb Lab right away

- Bomb lab available later today
 - What should you do before the exam?
 - Phases 1-3 of Bomb Lab
 - They are good practice for the kinds of assembly problems I'll put on the exam
 - Phases 4-6 are harder and can honestly wait
 - We'll talk about stuff in lectures on "Procedures" and "Pointers, Arrays, and Structs" that will help with this part
- Partner survey on Piazza
 - I'll start matching people today after I release Bomb Lab

Today's Goals

- Understand converting C control flow statements to assembly
 - If, If-else, While, For, etc.
- Discuss multiple ways to represent code
 - Often an efficiency tradeoff

Outline

- **Condition Codes**
- Branching (If/Else)
- Loops (Do While, While, For)
- Conditional Move

Condition codes

- Control is mediated via *Condition codes*
 - single-bit registers that record answers to questions about values
 - E.g., Is value x greater than value y? Are they equal? Is their sum even?
 - Let's keep "question" abstract for now. We'll see the details in a bit.
 - **Terminology:**
 - a bit is ***set*** if it is 1
 - a bit is ***cleared*** (or ***reset***) if it is 0

What are the condition codes?

- Condition codes on x86
 - **CF** Carry Flag (for unsigned)
 - **ZF** Zero Flag
 - **PF** Parity Flag
 - Not an arbitrary set! By combining them, can keep track of answers to many useful questions! (We'll see exactly which in a bit.)
- **SF** Sign Flag (for signed)
 - **OF** Overflow Flag (for signed)

Explicitly Setting Condition Codes: Compare

- `cmp{b,w,l,q} Src2, Src1`
- `cmpq src,dst` computes $t = dst - src$, ignoring the result
 - And sets condition codes along the way, like `subq` would!
 - Follows the rules we saw on the previous slide for arithmetic instructions
 - **Beware the order of the cmp operands!**
- Use cases
 - **ZF set** if $dst == src$
 - **SF set** if $(dst - src) < 0$ (as signed), i.e., $src > dst$ in a signed comparison!
 - **CF and OF** used mostly in combinations with others (see in a few slides)

Reading Condition Codes

- Cannot read condition codes directly; instead observe via instructions
 - And generally observe ***combinations*** of condition codes, not individual ones
- Example: the **setx** family of instructions
 - Write single-byte destination register based on combinations of condition codes
 - **set{e, ne, s, ...} D** where D is a 1-byte register
 - Example: **sete %al**
 - means: **%al=1** if flag ZF is set, **%al=0** otherwise

Condition codes combinations

Suffix	Description	Condition
e	Equal / Zero	ZF
ne	Not Equal / Not Zero	$\sim ZF$
s	Negative	SF
ns	Nonnegative	$\sim SF$
g	Greater (Signed)	$\sim (SF \wedge OF) \ \& \ \sim ZF$
ge	Greater or Equal (Signed)	$\sim (SF \wedge OF)$
l	Less (Signed)	$(SF \wedge OF)$
le	Less or Equal (Signed)	$(SF \wedge OF) \mid ZF$
a	Above (unsigned)	$\sim CF \ \& \ \sim ZF$
b	Below (unsigned)	CF

Note: suffixes do not indicate operand sizes, but rather conditions

These same suffixes will come back when we see other instructions that read condition codes.

Expect to be run after a **cmp**

What do you need to know?

- 90%+ of the time
 - cmp instruction followed by setx instruction (or a branch, next lecture)
 - Don't have to think about condition codes at all!
 - Think of as dst \times src
 - dst \leq src or dst \neq src etc.
- 10% or less of the time
 - Arbitrary arithmetic instruction sets the condition codes
 - Or testq sets the condition codes
 - Followed by a setx or branch (next section)
 - And you actually have to think about which condition codes are set to figure out what the assembly is doing, which can be challenging

Break + Practice

op src, dst

- **setX** asks the question: “Is destination **X** source?”
 - Usually condition codes from “`cmp source, destination`”
 - Don’t have to care about the exact values of the condition codes though
 - Just understand the logic

`%sil = 0x01`

`%dil = 0xF0`

`cmp %sil, %dil`

`seta %al`

`sete %al`

`setge %al`

SetX	Description
<code>sete</code>	Equal / Zero
<code>setne</code>	Not Equal / Not Zero
<code>sets</code>	Negative
<code>setns</code>	Nonnegative
<code>setg</code>	Greater (Signed)
<code>setge</code>	Greater or Equal (Signed)
<code>setl</code>	Less (Signed)
<code>setle</code>	Less or Equal (Signed)
<code>seta</code>	Above (unsigned)
<code>setb</code>	Below (unsigned)

Break + Practice

op src, dst

- set \mathbf{x} asks the question: “Is destination \mathbf{X} source?”
 - Usually condition codes from “`cmp source, destination`”
 - Don’t have to care about the exact values of the condition codes though
 - Just understand the logic

`%sil = 0x01`

`%dil = 0xF0`

`cmp %sil, %dil`

TRUE `seta %al # is %dil ABOVE %sil (unsigned)`

FALSE `sete %al # is %dil EQUAL to %sil`

FALSE `setge %al # is %dil GREATER or EQUAL to %sil (signed)`

Outline

- Condition Codes
- **Branching (If/Else)**
- Loops (Do While, While, For)
- Conditional Move

What can instructions do?

- Move data: ✓
- Arithmetic: ✓
- **Transfer control**
 - Instead of executing next instruction, go somewhere else

```
if (x > y)
    result = x-y;
else
    result = y-x;
```

```
while (x > y)
    result = x-y;
return result;
```

- Sometimes we want to go from the red code to the green code
- But the blue code is what's next!
- Need to transfer control! Execute an instruction that is not the next one
- And **conditionally**, too! (i.e., based on a condition)

Breaking with sequential execution

- “Normal” execution follows instructions in listed (sequential) order
 - To move to a different location – jump
 - Jump to different part of code depending on condition codes
 - Destination of a jump – label: particular address at which we find code
 - Label addresses are determined when generating the object code

```
Label for the jump .L9:  
    movq 8(%rsp), %rdx  
    movq 16(%rsp), %rax  
    cmpq %rax, %rdx  
    jle .L9 ← Jump if rdx <= rax  
    movl %rdx, %rax  
    ... other instructions ...
```

Jumping

- jX Instructions
 - Jump to different part of code depending on condition codes
 - `jmp` has two options
 - **Direct**: to a label (literal address)
 - **Indirect**: based on a register
 - Direct is by far the most common

jX	Condition	Description
<code>jmp</code>	1	Unconditional
<code>je</code>	<code>ZF</code>	Equal / Zero
<code>jne</code>	$\sim ZF$	Not Equal / Not Zero
<code>js</code>	<code>SF</code>	Negative
<code>jns</code>	$\sim SF$	Nonnegative
<code>jg</code>	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
<code>jge</code>	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
<code>jl</code>	$(SF \wedge OF)$	Less (Signed)
<code>jle</code>	$(SF \wedge OF) \mid ZF$	Less or Equal (Signed)
<code>ja</code>	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
<code>jae</code>	$\sim CF$	Above or Equal (unsigned)
<code>jb</code>	<code>CF</code>	Below (unsigned)
...

Documentation on all jump instructions: https://en.wikibooks.org/wiki/X86_Assembly/Control_Flow

Key idea: building C constructs with assembly

- Jump will let us build the flow control statements in C
 - If, While, For, Switch, etc.
- But the translation isn't always obvious
 - Might switch ordering, or negate the logical condition
 - Maintains the same result when it runs, but easier for assembly
- Steps
 1. Transform C into something simpler (closer to assembly)
 2. Transform simpler C into assembly

The “something simpler” is goto

- C allows `goto` as means of transferring control
 - Closer to machine-level programming style
 - Place labels wherever you want in code
 - Goto “jumps” to the referenced label
- Generally considered bad programming style
 - Makes it really difficult to understand what code is doing

```
int i = 0;
start:
    if (i >= 3) { goto end; }
    ++i;
    printf("Hello ");
    goto start;
end:
    printf("World! \n");
```

Prints:

“Hello Hello Hello World! \n”

Conditional Branch Example

```
long absdiff(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
long absdiff_j(long x, long y)
{
    long result;
    int ntest = (x <= y);
    if (ntest) { goto Else; }
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

- Translate an if statement into a “simpler” goto statement
 - Makes the if statement closer to machine code because goto can translate to jumps

Conditional Branch Example

Goto Version

```
long absdiff_j(long x, long y)
{
    long result;
    int ntest = (x <= y);
    if (ntest) {goto Else;}
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

Asm Version

```
absdiff:
    cmpq    %rsi, %rdi    # cmp x:y
    jle     .L2            # x <= y
    movq    %rdi, %rax
    subq    %rsi, %rax
    jmp     .L3
.L2:                                # jle target
    movq    %rsi, %rax
    subq    %rdi, %rax
.L3:
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Conditional Branch Example

Goto Version

```
long absdiff_j(long x, long y)
{
    long result;
    → int ntest = (x <= y);
    → if (ntest) {goto Else;}
        result = x-y;
        goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

Asm Version

```
absdiff:
    → cmpq    %rsi, %rdi    # cmp x:y
    → jle     .L2            # x <= y
        movq    %rdi, %rax
        subq    %rsi, %rax
        jmp     .L3
.L2:                                # jle target
        movq    %rsi, %rax
        subq    %rdi, %rax
.L3:
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Conditional Branch Example

Goto Version

```
long absdiff_j(long x, long y)
{
    long result;
    int ntest = (x <= y);
    if (ntest) {goto Else;}
    → result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

Asm Version

```
absdiff:
    cmpq    %rsi, %rdi    # cmp x:y
    jle     .L2            # x <= y
    → movq    %rdi, %rax
    → subq    %rsi, %rax
    jmp     .L3
.L2:
    movq    %rsi, %rax
    subq    %rdi, %rax
.L3:
    ret
```

jle target

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Conditional Branch Example

Goto Version

```
long absdiff_j(long x, long y)
{
    long result;
    int ntest = (x <= y);
    if (ntest) {goto Else;}
    result = x-y;
    → goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

Asm Version

```
absdiff:
    cmpq    %rsi, %rdi    # cmp x:y
    jle     .L2            # x <= y
    movq    %rdi, %rax
    subq    %rsi, %rax
    → jmp   .L3
.L2:
    movq    %rsi, %rax
    subq    %rdi, %rax
.L3:
    ret
```

jle target

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Conditional Branch Example

Goto Version

```
long absdiff_j(long x, long y)
{
    long result;
    int ntest = (x <= y);
    if (ntest) {goto Else;}
    result = x-y;
    goto Done;
Else:
    ➔ result = y-x;
Done:
    return result;
}
```

Asm Version

```
absdiff:
    cmpq    %rsi, %rdi    # cmp x:y
    jle     .L2            # x <= y
    movq    %rdi, %rax
    subq    %rsi, %rax
    jmp     .L3
.L2:
    ➔ movq    %rsi, %rax
    ➔ subq    %rdi, %rax
.L3:
    ret
```

jle target

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Conditional Branch Example

Goto Version

```
long absdiff_j(long x, long y)
{
    long result;
    int ntest = (x <= y);
    if (ntest) {goto Else;}
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
→ return result;
}
```

Asm Version

```
absdiff:
    cmpq    %rsi, %rdi    # cmp x:y
    jle     .L2            # x <= y
    movq    %rdi, %rax
    subq    %rsi, %rax
    jmp     .L3
.L2:
    movq    %rsi, %rax
    subq    %rdi, %rax
.L3:
→ ret
```

jle target

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

General “if-then-else” translation

C Code

```
if (test-expr)
    then-statement
else
    else-statement
```

Goto Version

```
ntest = ! (test-expr);
if (ntest) {
    goto Else;
}
then-statement;
goto done;
Else:
    else-statement;
done:
```

- *test-expr* is an expression returning integer
 - = 0 interpreted as false, ≠0 interpreted as true
- Only one of the two statements is executed
 - i.e. only one of the two *branches* of code
- That’s one translation; there are others
 - E.g., flipping the order of the blocks instead of flipping the test
- Conditional expressions ($x ? y : z$) can use the same translation

If statement - bigger example

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

If statement - bigger example

a→%rdi, b→%rsi, c→%rax

```
long test(long a, long b) {          cmp %rsi, %rdi
    long c;                         jle elif      # !(a > b)
    if (a > b) {                   movq $1, %rax
        c = 1;                      jmp end
    } else if (a < b) {             elif:
        c = -1;                     cmp %rsi, %rdi
    } else {                        jge else      # !(a < b)
        c = 0;                      movq $-1, %rax
    }                                jmp end
    return c;                       else:
}                                     movq $0, %rax
                                    end:
                                    ret           # returns %rax
```

If statement - bigger example

a→%rdi, b→%rsi, c→%rax

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

```
cmp %rsi, %rdi  
jle elif          # !(a > b)  
movq $1, %rax  
jmp end  
elif:  
cmp %rsi, %rdi  
jge else          # !(a < b)  
movq $-1, %rax  
jmp end  
else:  
movq $0, %rax  
end:  
ret               # returns %rax
```

If statement - bigger example

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

a→%rdi, b→%rsi, c→%rax

```
    cmp %rsi, %rdi  
    jle elif      # !(a > b)  
    movq $1, %rax  
    jmp end  
  
elif:  
    cmp %rsi, %rdi  
    jge else      # !(a < b)  
    movq $-1, %rax  
    jmp end  
  
else:  
    movq $0, %rax  
  
end:  
    ret           # returns %rax
```

If statement - bigger example

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

a→%rdi, b→%rsi, c→%rax

```
    cmp %rsi, %rdi  
    jle elif      # !(a > b)  
    movq $1, %rax  
    jmp end  
  
elif:  
    cmp %rsi, %rdi  
    jge else      # !(a < b)  
    movq $-1, %rax  
    jmp end  
  
else:  
    movq $0, %rax  
  
end:  
ret          # returns %rax
```

If statement - bigger example

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

a→%rdi, b→%rsi, c→%rax

```
    cmp %rsi, %rdi  
    jle elif      # !(a > b)  
    movq $1, %rax  
    jmp end  
  
elif:  
    cmp %rsi, %rdi  # unnecessary  
    jge else      # !(a < b)  
    movq $-1, %rax  
    jmp end  
  
else:  
    movq $0, %rax  
  
end:  
    ret           # returns %rax
```

Break + Optimization (O1)

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

a → %rdi, b → %rsi, c → %rax

```
    movq $1, %rax  
    cmp %rsi, %rdi  
    jg end  
    setl %al  
    movzbq %al, %rax  
    neg %rax  
end:  
    ret  
# returns %rax
```

What is the yellow code block doing above?

Break + Optimization (O1)

```
long test(long a, long b) {  
    long c;  
    if (a > b) {  
        c = 1;  
    } else if (a < b) {  
        c = -1;  
    } else {  
        c = 0;  
    }  
    return c;  
}
```

a→%rdi, b→%rsi, c→%rax

```
    movq $1, %rax  
    cmp %rsi, %rdi  
    jg end  
    setl %al  
    movzbq %al, %rax  
    neg %rax  
end:  
    ret
```

returns %rax

else if and else together

What is the yellow code block doing above?
Generates 0 (not less) or -1 (less)

Indirect jump

- `jmp *0x40000(%rdi, %rdx, 8)`
 - Calculate memory address: $0x40000 + \%rdi + 8 * \%rdx$
 - Then load value from that memory address
 - Jump to *that* value
- Indirect jumps jump to the address loaded from memory
 - Essentially a function pointer
 - Or used for a Jump Table: efficient switch statements (see bonus slides)
- The * lets you know that something tricky is going on
 - Displacement could be a label rather than a value

Outline

- Condition Codes
- Branching (If/Else)
- **Loops (Do While, While, For)**
- Conditional Move

Loops

- C provides different looping constructs
 - `while`, `do ... while`, `for`
- No corresponding instruction in machine code
- Most compilers
 1. Transform general loops into `do ... while`

```
do  
  body-statement  
  while (test-expr) ;
```

Do-while:

Same idea as a while loop, but the body always runs at least once

2. Rewrite that with `goto`
3. Then compile them into machine code

“Do-While” Loop Example

- Running example: count number of 1s in x (“popcount”)
 - We’ll write it with different kinds of loops
 - What the body of the loop does is not our focus; we’ll just ignore it

C Code

```
long pcount_do
(unsigned long x)
{
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

“Do-While” Loop Compilation

- Step 1: translate do-while into a gotos
- Use conditional branch to either continue looping or to exit loop

C Code

```
long pcount_do  
  (unsigned long x)  
{  
    long result = 0;  
    do {  
        result += x & 0x1;  
        x >>= 1;  
    } while (x);  
    return result;  
}
```

Goto Version

```
long pcount_goto  
  (unsigned long x)  
{  
    long result = 0;  
    loop:  
        result += x & 0x1;  
        x >>= 1;  
    if (x) {goto loop;}  
    return result;  
}
```

“Do-While” assembly translation

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
if (x) {goto loop;}
return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

→ .L2:

movq \$0,%rax # result = 0
loop:
movq %rdi,%rdx
andq \$1,%rdx # t = x & 0x1
addq %rdx,%rax # result += t
shrq %rdi # x >>= 1
jne .L2 # if (x) goto loop
rep; ret

“Do-While” assembly translation

Goto Version

```
long pcount_goto  
    (unsigned long x) {  
        long result = 0;  
loop:  
        result += x & 0x1;  
        x >>= 1;  
if (x) {goto loop;}  
        return result;  
    }
```

Register	Use(s)
%rdi	Argument x
%rax	result

→ .L2:
 movq \$0,%rax # result = 0
 movq %rdi,%rdx
 andq \$1,%rdx # t = x & 0x1
 addq %rdx,%rax # result += t
 shrq %rdi # x >>= 1
 jne .L2 # if (x) goto loop
 rep; ret

Which instruction sets the condition codes for jne?

Logical shift right (`shrq`)

– the test is whether the result is 0 or not

“Do-While” assembly translation

Goto Version

```
long pcount_goto  
    (unsigned long x) {  
        long result = 0;  
  
    loop:  
        result += x & 0x1;  
        x >>= 1;  
    if (x) {goto loop;}  
    return result;  
}
```

→ .L2:

	movq	\$0,%rax	# result = 0
			# loop:
	movq	%rdi,%rdx	
	andq	\$1,%rdx	# t = x & 0x1
	addq	%rdx,%rax	# result += t
	shrq	%rdi	# x >>= 1
	jne	.L2	# if (x) goto loop
	rep;	ret	

- rep instruction repeats string operations following it **What?!!**

“Do-While” assembly translation

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
if (x) {goto loop;}
return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

→ .L2:

movq \$0,%rax # result = 0
loop:
movq %rdi,%rdx
andq \$1,%rdx # t = x & 0x1
addq %rdx,%rax # result += t
shrq %rdi # x >>= 1
jne .L2 # if (x) goto loop

rep; ret

- **rep** instruction repeats string operations following it **What?!!**
- **rep; ret** uses **rep** as a no-op (a.k.a nop, an operation that does nothing)
 - Example of a compiler optimization that you might run into in real assembly code
 - AMD recommends this to speed up execution when there is a jump before a return
 - See CE361 and CE452 for more details (Computer Architecture courses)

General “Do-While” Translation

- Body: {
Statement₁;
Statement₂;
...
Statement_n;
}

C Code

```
do  
  Body  
  while ( Test );
```

Goto Version

```
loop:  
  Body  
  if ( Test ) {  
    goto loop  
  }
```

- Test returns integer
 - = 0 interpreted as false
 - ≠ 0 interpreted as true

General “While” Translation #1

- “Jump-to-middle” translation
- Most straightforward match to how “while” works

While version

```
while ( Test ) {  
    Body  
}
```



Goto Version

```
goto test;  
loop:  
    Body  
test:  
    if ( Test ) {  
        goto loop;  
    }
```

While Loop Example #1

C Code

```
long pcount_while
(unsigned long x)
{
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle

```
long pcount_goto_jtm
(unsigned long x)
{
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) {goto loop;}
    return result;
}
```

- Initial goto starts loop at test

Comparing while to do-while

While with goto (jump to middle)

```
long pcount_while_goto_jtm
(unsigned long x)

{
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) {goto loop;}
    return result;
}
```

Do While with goto

```
long pcount_dowhile_goto
(unsigned long x)

{
    long result = 0;

loop:
    result += x & 0x1;
    x >>= 1;

    if (x) {goto loop;}
    return result;
}
```

General “While” Translation #2

While version

```
while ( Test)  
    Body
```

- “Do-while” conversion
- More optimized compiler translation

Do-While Version

```
if ( ! Test )  
    goto done;  
do  
    Body  
    while( Test );  
done:
```

Goto Version

```
if ( ! Test )  
    goto done;  
loop:  
    Body  
    if ( Test )  
        goto loop;  
done:
```

“While” Loop Example #2

C Code

```
long pcount_while
(unsigned long x)
{
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Goto Version

```
long pcount_goto_dw
(unsigned long x)
{
    long result = 0;
    if (!x) {goto done;}
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) {goto loop;}
done:
    return result;
}
```

- Initial conditional guards entrance to loop

Comparing jump-to-middle and guarded-do-while

While with goto (jump to middle)

```
long pcount_while_goto_jtm
(unsigned long x)

{
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) {goto loop;}
    return result;
}
```

While with goto (guarded do-while)

```
long pcount_goto_dw
(unsigned long x)

{
    long result = 0;
    if (!x) {goto done;}
loop:
    result += x & 0x1;
    x >>= 1;

    if(x) {goto loop;}
done:
    return result;
}
```

“For” Loop Form

General Form

```
for (Init; Test; Update)
```

Body

```
#define WSIZE 8*sizeof(int)
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit = (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{
    unsigned bit = (x >> i) & 0x1;
    result += bit;
}
```

“For”→“While”→“Do-While”→“Goto”


For Version

```
for (Init; Test; Update)  
    Body
```




While Version

```
Init;  
while (Test) {  
    Body  
    Update;  
}
```



Goto Version

```
Init;  
if (!Test)  
    goto done;  
loop:  
    Body  
    Update;  
    if (Test)  
        goto loop;  
done:
```



Do-While Version

```
Init;  
if (!Test)  
    goto done;  
do {  
    Body  
    Update;  
} while (Test)  
done:
```

“For” Loop Conversion Example

C Code

```
#define WSIZE 8*sizeof(int)
long pcount_for(unsigned x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++) {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

Goto Version

```
#define WSIZE 8*sizeof(int)
long pcount_for_gt(unsigned x)
{
    size_t i;
    long result = 0;
    i = 0; Init
    if (!(i < WSIZE)) ! Test
        goto done;
loop:
{
    unsigned bit =
        (x >> i) & 0x1;
    result += bit;
}
i++; Update
if (i < WSIZE) Test
    goto loop;
done:
    return result;
}
```

Break + Assembly to loop

What does this function do?

```
my_function:      # %rdi is argument1
                  mov $0, %rax
                  mov $0, %rbx
                  test %rdi, %rdi
                  je end

loop:
                  add %rbx, %rax
                  add $1, %rbx
                  cmp %rdi, %rbx
                  jne loop

end:
                  ret          # returns %rax
```

Assembly to loop

```
my_function:      # %rdi is argument1
    mov $0, %rax      # clear variables
    mov $0, %rbx
    test %rdi, %rdi
    je end            # skip loop if %rdi is 0
loop:
    add %rbx, %rax
    add $1, %rbx
    cmp %rdi, %rbx
    jne loop
end:
    ret               # returns %rax
```

Assembly to loop

```
my_function:      # %rdi is argument1
    mov $0, %rax      # clear variables
    mov $0, %rbx
    test %rdi, %rdi
    je end            # skip loop if %rdi is 0
loop:
    add %rbx, %rax
    add $1, %rbx
    cmp %rdi, %rbx
    jne loop
end:
    ret               # returns %rax
```

Assembly to loop

```
my_function:          # %rdi is argument1
    mov $0, %rax      # clear variables
    mov $0, %rbx
    test %rdi, %rdi
    je end            # skip loop if %rdi is 0

loop:
    add %rbx, %rax   # %rax += %rbx
    add $1, %rbx      # %rbx += 1

    cmp %rdi, %rbx
    jne loop

end:
    ret               # returns %rax
```

Assembly to loop

```
my_function:          # %rdi is argument1
    mov $0, %rax      # clear variables
    mov $0, %rbx
    test %rdi, %rdi
    je end            # skip loop if %rdi is 0

loop:
    add %rbx, %rax   # %rax += %rbx
    add $1, %rbx      # %rbx += 1
    cmp %rdi, %rbx
    jne loop           # while %rbx != %rdi

end:
    ret               # returns %rax
```

Assembly to loop

```
long my_function(long rdi) {  
    long rax = 0;  
    long rbx = 0;  
  
    while (rbx != rdi) {  
        rax += rbx;  
        rbx += 1;  
    }  
  
    return rax;  
}
```

```
my_function:      # %rdi is argument1  
    mov $0, %rax      # clear variables  
    mov $0, %rbx  
    test %rdi, %rdi  
    je end            # skip loop if %rdi is 0  
loop:  
    add %rbx, %rax    # %rax += %rbx  
    add $1, %rbx       # %rbx += 1  
    cmp %rdi, %rbx  
    jne loop           # while %rbx != %rdi  
end:  
    ret                # returns %rax
```

Assembly to loop

```
long my_function(long rdi) {  
    long rax = 0;  
    long rbx = 0;  
  
    while (rbx != rdi) {  
        rax += rbx;  
        rbx += 1;  
    }  
  
    return rax;  
}  
  
long my_function(long max) {  
    long result = 0;  
    for (long i=0; i<max; i++) {  
        result += i;  
    }  
  
    return result;  
}
```

```
my_function:          # %rdi is argument1  
    mov $0, %rax      # clear variables  
    mov $0, %rbx  
    test %rdi, %rdi  
    je end            # skip loop if %rdi is 0  
loop:  
    add %rbx, %rax    # %rax += %rbx  
    add $1, %rbx       # %rbx += 1  
    cmp %rdi, %rbx  
    jne loop           # while %rbx != %rdi  
end:  
    ret                # returns %rax
```

Outline

- Condition Codes
- Branching (If/Else)
- Loops (Do While, While, For)
- **Conditional Move**

The Problem with Conditional Jumps

- Conditional jumps = conditional *transfer of control*
 - i.e., forget what you thought you were going to do, do this other thing instead
- Modern processors like to do work “ahead of time”
 - Keywords: ***pipelining, branch prediction, speculative execution***
 - Transfer of control may mean throwing that work away
 - That’s inefficient
- Solution: conditional *moves*
 - We still get to do something conditionally
 - But no transfer of control necessary
 - “Ahead of time” work can always be kept

Conditional Moves

cmovX	Description
cmove S, D	equal / Zero
cmovne S, D	not equal / Not zero
cmovs S, D	negative
cmovns S, D	nonnegative
cmovg S, D	greater (Signed)
cmovge S, D	greater or equal (Signed)
cmovl S, D	less (Signed)
cmovle S, D	less or equal (Signed)
cmovea S, D	above (Unsigned)
cmoveae S, D	above or equal (Unsigned)
cmovb S, D	below (Unsigned)
cmovbe S, D	below or equal (Unsigned)

$D \leftarrow S$ only if
test condition
is true

Conditional Move Example

```
long absdiff(long x, long y)
{
    long res;
    if (x > y)
        res = x-y;
    else
        res = y-x;
    return res;
}
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

absdiff:

```
    movq    %rdi, %rax    # res = x
    subq    %rsi, %rax    # res = x-y
    movq    %rsi, %rdx
    subq    %rdi, %rdx    # alt = y-x
    cmpq    %rsi, %rdi    # cmp x:y
    cmovle %rdx, %rax    # if x<=y, res = alt
    ret
```

Look Ma, no branching!

Must compute both results, though, which is not always possible or desirable...

Bad Cases for Conditional Move

Expensive Computations

- Both values get computed
- Only makes sense when computations are very simple

```
val = Test(x) ? Hard1(x) : Hard2(x);
```

Risky Computations

- A `cmove` requires that both values get computed
- Could trigger a fault (compiler must use jumps instead)

```
val = p ? *p : 0;
```

Computations with side effects

```
val = x > 0 ? x++ : x--;
```

- Both values get computed
- Needs use extra temporary registers to hold intermediate results

If, else if, else – optimized (O3) a→%rdi, b→%rsi, c→%rax

```
long test(long a, long b) {          movq $0, %rax    # clear reg
    long c;                         cmp %rsi, %rdi
    if (a > b) {                   movq $1, %rdx
        c = 1;                      setl %al      else if and else
    } else if (a < b) {             neg %rax     together
        c = -1;                     cmp %rsi, %rdi
    } else {                        cmove %rdx, %rax   (%al is %rax)
        c = 0;                      ret           select output
    }
    return c;
}
```

Outline

- Condition Codes
- Branching (If/Else)
- Loops (Do While, While, For)
- Conditional Move

- Bonus Slides
 - Switch Statements and Jump Tables

Switch statements

- A multi-way branching capability based on the value of an integer
- Useful when many possible outcomes
- Switch cases
 - Fall through cases:
 - Here 1
 - Missing cases:
 - Here 3, 4, 5, 6
 - Multiple case labels:
 - Here 7 & 8
- Easier to read C code and more efficient implementation with jump tables

```
long switch_fun
(long x, long y, long z, long w) {
    switch(x) {
        case 0:
            w += y;
            break;
        case 1:
            w -= y;
            /* FALL THROUGH */
        case 2:
            w += z;
            break;
        /* MISSING CASES */
        case 7:
        case 8: /* MULTIPLE CASES */
            w -= z;
            break;
        default:
            w = 2;
            break;
    }
    w += 5;
    return w;
}
```

Target code blocks

```
case 0:  
    w += y;  
    break;  
case 1:  
    w -= y;  
    /* FALL THROUGH */  
case 2:  
    w += z;  
    break;  
case 7:  
case 8: /* MULTIPLE CASES */  
    w -= z;  
    break;  
default:  
    w = 2;  
    break;
```

One code block per case!

```
.L7:          # case 0  
    addq    %rsi, %rcx  
    jmp     .L2           # break  
  
.L6:          # case 1  
    subq    %rsi, %rcx  
    # FALL THROUGH  
.L5:          # case 2  
    addq    %rdx, %rcx  
    jmp     .L2           # break  
  
.L3:          # cases 7 and 8  
    subq    %rdx, %rcx  
    jmp     .L2           # break  
  
.L8:          # default  
    movl    $2, %ecx  
    jmp     .L2           # break  
  
.L2:  
    ...
```

%rdi	Argument X
%rsi	Argument Y
%rdx	Argument Z
%rcx	Argument W
%rax	Return value

break becomes a jump to after the **switch** (.L2)!

Jump tables

Switch statement


```
switch(x) {  
    case 0:  
        Block 0  
    case 1:  
        Block 1  
    . . .  
    case n-1:  
        Block n-1  
}
```

- Definition: An array where entry i is the address of the code segment to run when the switch variable equals i

Jump table (data in memory)

jtab:	Targ_0
	Targ_1
	Targ_2
	•
	•
	•
	Targ_n-1

Jump targets (code in memory)



Approx. translation:

```
target = jtab[x];  
goto *target;
```


- Register `%rdi` holds the switch variable x
- `jtab` is the address of the jump table

Q1: which *table entry* holds the *address* of the next instruction? **The x^{th} (or $\%rdi^{\text{th}}$)**

Q2: what is the memory address *of that entry*? **$jtab + \%rdi * 8$**

Q3: what is the address *of the next instruction* to execute? **$M[jtab + \%rdi * 8]$**

Jump table for our example



Putting it all Together

Jump table

(addresses of code blocks)

```
long switch_fun (...) {  
    switch(x) {  
        // cases 0,1,2,7,8  
        // and default  
    }  
    w += 5;  
    return w;  
}
```

%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rcx	Argument w
%rax	Return value

```
.L4:  
.quad .L7 # x=0  
.quad .L6 # x=1  
.quad .L5 # x=2  
.quad .L8 # x=3  
.quad .L8 # x=4  
.quad .L8 # x=5  
.quad .L8 # x=6  
.quad .L3 # x=7  
.quad .L3 # x=8
```

```
switch_fun:  
    cmpq    $8, %rdi      # compare x to 8  
    ja     .L8            # above 8 (outside table!) -> default  
    jmp    * .L4(,%rdi,8) # goto *Jtab[x], a.k.a M[.L4 + x*8]  
                                # * means an indirect jump (like dereference)
```



Indirect jump: look up address in memory; jump there

```

long switch_fun
(long x, long y, long z, long w) {
    switch(x) {
        case 0:
            w += y;
            break;
        case 1:
            w -= y;
            /* FALL THROUGH */
        case 2:
            w += z;
            break;
        /* MISSING CASES */
        case 7:
        case 8: /* MULTIPLE CASES */
            w -= z;
            break;
        default:
            w = 2;
            break;
    }
    w += 5;
    return w;
}

```

Full assembly code for our example

```

switch_fun:
    cmpq    $8, %rdi
    ja     .L8
    jmp    * .L4(,%rdi,8)
.L4:
    .quad   .L7
    .quad   .L6
    .quad   .L5
    .quad   .L8
    .quad   .L8
    .quad   .L8
    .quad   .L8
    .quad   .L3
    .quad   .L3
.L7:
    addq    %rsi, %rcx
    jmp    .L2
.L6:
    subq    %rsi, %rcx
    # FALL THROUGH
.L5:
    addq    %rdx, %rcx
    jmp    .L2
.L3:
    subq    %rdx, %rcx
    jmp    .L2
.L8:
    movl    $2, %ecx
    jmp    .L2
.L2:
    leaq    5(%rcx), %rax
    ret

```

Another Jump Table Example: starting with assembly

- QUIZ: find the address of the jump table and code blocks

- `linux> objdump -d prog`
- The jump table starts at address `0x400668`
- The `default` code block is at address `0x40055c`

```
0000000000400528 <switch_eg>:  
400528: 48 89 d1          mov    %rdx,%rcx  
40052b: 48 83 ff 06       cmp    $0x6,%rdi  
40052f: 77 2b              ja    40055c <switch_eg+0x34>  
400531: ff 24 fd 68 06 40 00 jmpq   *0x400668(%rdi,8)
```

Note: these are hex values (memory addresses for instructions)
objdump does not put 0x in front of instruction addresses when it disassembles

How would you find the address of the other code blocks?

Object code: Jump Table


- Jump table
 - Doesn't show up in disassembled code
 - Can inspect using GDB: examine data starting at address **0x400668**

```
gdb prog  
(gdb) x/7xg 0x400668
```

- Examine **7** hexadecimal format "giant words" (8-bytes each)
- Use command "**help x**" to get format documentation

0x400668:

```
0x000000000040055c  
0x0000000000400538  
0x0000000000400540  
0x000000000040054a  
0x000000000040055c  
0x0000000000400553  
0x0000000000400553
```



How can you see the code for each one of the target code blocks?

Object code: Disassemble targets

```
.section .rodata
.align 8
.L4:
.quad .L8 # x = 0
.quad .L3 # x = 1
.quad .L5 # x = 2
.quad .L9 # x = 3
.quad .L8 # x = 4
.quad .L7 # x = 5
.quad .L7 # x = 6
```

0x40055c	400538:	48 89 f0	mov %rsi,%rax
0x400538	40053b:	48 0f af c2	imul %rdx,%rax
0x400540	40053f:	c3	retq
0x40054a	400540:	48 89 f0	mov %rsi,%rax
0x40055c	400543:	48 99	cqto
0x400553	400545:	48 f7 f9	idiv %rcx
0x400553	400548:	eb 05	jmp 40054f <switch_eg+0x27>
0x40054a	40054a:	b8 01 00 00 00	mov \$0x1,%eax
0x40055c	40054f:	48 01 c8	add %rcx,%rax
0x400553	400552:	c3	retq
0x400553	400553:	b8 01 00 00 00	mov \$0x1,%eax
0x400558	400558:	48 29 d0	sub %rdx,%rax
0x40055b	40055b:	c3	retq
0x40055c	40055c:	b8 02 00 00 00	mov \$0x2,%eax
0x400553	400561:	c3	retq

linux> gdb prog
(gdb) disassemble 0x400538,0x400562

Object code: Disassemble targets

0x40055c

0x400538

0x400540

0x40054a

0x40055c

0x400553

0x400553

400538:	48 89 f0	mov %rsi,%rax
40053b:	48 0f af c2	imul %rdx,%rax
40053f:	c3	retq
400540:	48 89 f0	mov %rsi,%rax
400543:	48 99	cqto
400545:	48 f7 f9	idiv %rcx
400548:	eb 05	jmp 40054f <switch_eg+0x27>
40054a:	b8 01 00 00 00	mov \$0x1,%eax
40054f:	48 01 c8	add %rcx,%rax
400552:	c3	retq
400553:	b8 01 00 00 00	mov \$0x1,%eax
400558:	48 29 d0	sub %rdx,%rax
40055b:	c3	retq
40055c:	b8 02 00 00 00	mov \$0x2,%eax
400561:	c3	retq

```
long w = 1;
switch(x) {
    case 1:          /* .L3 */
        w = y * x;
        break;
    case 2:          /* .L5 */
        w = y/z;
        /* fall through */
    case 3:          /* .L9 */
        w += z;
        break;
```

```
.....
case 5:
    case 6:          /* .L7 */
        w -= z;
        break;
default:          /* .L8 */
    w = 2;
}
```

Object code: Memory View

